

UPM Raflatac Technical Information

23-06-2025 EN SI

Product	RAFLAMATT-FSC / PERM.GREENTAC + / KRAFT SPECIAL 90 / SCORE PRINTED
Sales Code	GQU/SP34/14/W3
Product use	Product designed for high-quality and finely detailed labels with multicolour printing and a matt finish. Especially recommended for product and promotional labeling.

Typical technical values

Face	RAFLAMATT-FSC		
Product	White, matt, machine coated, woodfree label paper.		
Substance	80	g/m ²	ISO 536
Caliper	70	µm	ISO 534
Tensile strength MD	5	kN/m	ISO 1924/1
Tensile strength CD	2	kN/m	ISO 1924/1
Brightness	97	%	ISO 2470/1
Roughness	2,4	µm	ISO 8791 PPS 10
Opacity	93	%	ISO 2471
Gloss	20	%	Hunter 75°
Printability	Offset, flexography, letterpress.		
Sustainability	The product is sold as FSC Mix Credit under UPM Raflatac's FSC™ certificate SGSCH-COC-004879.		
Adhesive	SP34 GREENTAC PLUS		
Type	General permanent adhesive for sheets.		
Composition	Modified acrylic dispersion.		
Tack	10	N	FTM 9
Shear min	2	h	FTM 8
Backing	KRAFT SPECIAL 90		
Product	White woodfree kraft backing paper.		
Substance	86	g/m ²	ISO 536
Caliper	87	µm	ISO 534
Tensile strength MD	8,7	kN/m	ISO 1924
Tensile strength CD	3,8	kN/m	ISO 1924

Performance

Total caliper	173 µm ± 10%
Minimum labelling temperature	5 °C
Service temperature	-10 to 100 °C
Shelf life	From date of manufacture: 48 months, under FINAT defined storage conditions (+20-25°C and RH 40-50%). Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.

Information

Product Information	Scoring is crucial to ensuring self-adhesive labels are easily peeled away from their backing. Our sheets have folding scores that are spaced at 35 mm intervals, what enables a smooth label opening. Scores open after bending 90-120° Scores don't open if they have not been folded previously.
Product availability	Standard range. (Other sizes and/or components available upon request).

STANDARD SHEET SIZE (CM)	50x70
PACKAGING TYPE	Ream wrapped / Bulk

Approvals

Approvals	For further compliance information related to food labeling applications, please contact your local sales representative for a Declaration of Conformance (DoC) document.
Approvals	Toy labeling: This product complies with the European Standard EN71-3:2013 "Safety of Toys" - Migration of certain elements.
Disclaimer	The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.

